

# MiMI: Michigan Molecular Interactions




Adriane Chapman, Magesh Jayapandian, Cong Yu, Glenn Tarcea, H. V. Jagadish University of Michigan, Ann Arbor, Michigan, USA



## **Overview**

- Goal: Effective integration and retrieval of biological data from multiple sources
- Deep Merge
- Integrates heterogeneous and complimentary data sources
- Facilitates provenance-tracking and supports probabilistic manipulation of
- Query Interface
- Supports standard query interfaces: Keyword, Browse, and XQuery
- MQuery: A flexible query interface providing functionalities with minimum
- NaLIX: A Natural Language Interface to Query XML
- Features
- Provenance Tracking
- Probability Manipulation
- Homologue-based Interaction Prediction
- Available At: http://mimi.ctaalliance.org

## **System Architecture**




## **Acknowledgements**

- · University of Michigan
  - Medical School: Philip Andrews; Brian Athey; David States
  - Department of Electrical Engineering and Computer Science: Jignesh Patel
  - Department of MCDB: Anui Kumai
  - School of Information: Dragomir Radev - Department of Linguistics: Steve Abney
- Wayne State University
- Thanks to the following groups for sharing their data
- Samuel Lunenfeld
- Research Institute
- Cold Spring Harbor Laboratory, - European Bioinformatics Institute
- Center for Cancer Systems Biology at Harvard
- Max Delbueck Center
- Gene Ontology Consortium
- Johns Hopkins University / Institute of Bioinformatics
- Mt. Sinai Hospital / Blueprint - NCBI
- Sanger Institute
- UCLA
- - NSF grant IIS-0219513, NIH project 1-U54-DA021519-01A1, NSF through a graduate fellowship


## **Deep Merge**

## **Heterogeneous Sources**



#### BIND

#### **InterPro**




#### **HPRD**

## **Merging Guidelines**

- Preserve all data
- Maintain provenance
- Utilize an identity function to determine whether two objects are fundamentally the same in the real world and should be consolidated
- 9,860 Center for Cancer Systems Biology Records
- 287,072 BIND Records
- 94,533 HPRD Records
- 73,561 DIP Records
- 69,065 GRID Records
- 130,622 IntAct Records
- 5.178 Max Delbrueck Center Records
- 89,662 Reactome Records

## MiMI Records



### **Statistics**

- Sources
- Interaction Data: Center for Cancer Systems Biology Dataset, BIND, DIP, HPRD, GRID, IntAct, Max Delbrueck Center Dataset
- Pathyway Data: Reactome
- Auxiliary Data: GO, OrganelleDB, OrthoMCL, Pfam, ProtoNet, miBlast, InterPro, IPI

## **Query Interface**

### Components

#### Traditional

- Browse: Enables users to trawl through records of interest
- Keyword: Facilitates easy lookup of a particular record
- **XQuery**: Permits users to write their own sophisticated XQuery

#### MQuery


- Allows users to point-and-click queries
- Teaches users by example how to use XQuery

#### NaLIX

[RPO21] -- [RPB5]

 An extension that allows users to write natural language queries against the database

**MQuery Interface** 





- Any web browser can be used to load the interface
- Supported query operations include selection, projection, join, and sorting

## **MQuery Advantages**

- Simplicity
  - Users pose declarative queries in XQuery without prior knowledge of
    - XQuery syntax
    - Schema of the database
- Expressivity
  - MQuery is more expressive than traditional (static) form-based interfaces which are typically ad hoc and non-extensible
- Compatibility
  - MQuery is HTML-based and can be loaded and viewed on any standard web-browser

## **Provenance and Probability**

- Provenance
- Tracks data origin
- Describes manipulations being performed
- Enables users to decide which sources they trust and wish to retrieve
- Probability
- Utilizes reported false positive/negative rates of experiments as base probabilities
- Deduces the probability of an interaction based on base probabilities using standard probability model
- Allows users to adjust the default probabilities of given experiments or interaction

## **Features**



